



**ENGINEERED
MINERALS**

J.M. Huber Corporation

One Huber Road
Macon, GA 31298
912 745-4751
Fax 912 745-1116 - Marketing
Fax 912 741-1817 - R & D/Tech Services
Fax 912 742-8613 - All Others
Telex 544438

J. M. HUBER

Page 1 of 5

MATERIAL SAFETY DATA SHEET

Information contained in this form is proprietary and is furnished solely for the use of our customers. The information is believed to be reliable. No guarantee is implied or expressed regarding the accuracy of this information or the use of the product since the conditions for use are beyond our control. Nothing contained herein should be construed as a recommendation to use this product in conflict with existing patents covering any material or its use.

Doc#: 930802-0240

SECTION I: IDENTIFICATION

Group Name : KC01
 : CALCINED WW KAOLIN
 Trade Name : POLYFIL 80®
 Chemical Name : ANHYDROUS ALUMINUM SILICATE
 (Synonyms) : (CALCINED KAOLIN; CALCINED CHINA CLAY)
 Manufacturer : J. M. Huber Corporation
 : Clay Division
 Address : One Huber Road
 City, State, Zip: Macon, GA 31298
 Telephone Number: 912-745-4751

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENTS:	CAS #	Min	Max
CALCINED KAOLIN	66402-68-4	97.50 %	99.50 %
TITANIUM DIOXIDE	13463-67-7	0.50 %	2.50 %

 Amorphous calcined kaolin (anhydrous aluminum silicate) is produced by heating naturally-occurring crystalline kaolin (hydrated aluminum silicate) to very high temperatures.

Additional Information:

Above ingredient percentages are representative of bulk samples.

Date MSDS Created: 13-AUG-91 Prepared by: JAY HUTTO, EKVIR.MGR ; Phone: 912-745-4751
 Date Last Revised: 02-AUG-93
 For Routine Inquiries Contact: Technical Services Dept. ; Tech Service Coordinator ; 912-745-4751

[Signature] 8/2/93

MARKETED BY
**HARWICK STANDARD
 DISTRIBUTION CORPORATION**
 60 S. Seiberling Street · Akron, Ohio 44305

SECTION II.A: OTHER INGREDIENTS

**** Additives or ingredients which MAY be present, and which might be of industrial hygiene interest:**

****CRYSTALLINE SILICA (Quartz) - Less than 0.1% respirable.**

SECTION III: PHYSICAL CHARACTERISTICS

PHYSICAL DATA:	Qty.	Units	Text
Specific Gravity:			2.5 - 2.7
Melting Point:	1700	DEGC	Approximately
pH Concentration:			5.0 - 7.0 at 28% solids.
Solubility Data:			Negligible
Appearance and Odor:			
White powder with negligible odor.			

SECTION IV: HEALTH HAZARD DATA

Tolerance Limits:

Ingredients	Agency	Test	Concentration
-------------	--------	------	---------------

*** No Tolerance Limits Specified ***

Skin Contact-	Non-hazardous	Historical	
Skin Absorpt-	Non-hazardous	Historical	
Eye-	Nuisance Dust	Historical	
Ingestion-	Non-hazardous	Historical	
Inhalation-			

* Dust OSHA PEL = See 29 CFR 1910.1000
Tables Z-1-A and Z-3.

ACGIH TLV =10 mg/cu.meter (Total Dust).

SOURCE: ACGIH TLV's-Threshold Limit Values for Chem. Substances.

EFFECTS OF EXPOSURE:**Acute:**

* No acute effects. Brief exposures to nuisance dust concentrations above the 8-hour recommended Threshold Limit Value (TLV) should pose no acute health problems.

Chronic:

* As is true with any kaolin clay, long term overexposure to high concentrations of this dust without the use of a dust mask may produce X-ray evidence of dust in the lungs. Continued long term overexposure may affect respiratory function in some individuals.

*NOTE: The above Hazard Determination is based on NON-CALCINED kaolin dust. Kaolin dust has been the subject of several epidemiological studies. Historical experience suggests that the hazards of calcined kaolin are similar.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Unknown.

EMERGENCY AND FIRST AID PROCEDURES:

Skin-	No special precautions; flush with water.
Eye-	No special precautions; flush with water.
Ingestion-	No special precautions.
Inhalation-	No special precautions.

SECTION V: FIRE & EXPLOSION HAZARDS

(Flammability Classification)

Additional Information:

This product is NOT a fire hazard or an explosive hazard in either the powder or slurry form. No special fire fighting procedures or extinguishing media are required. Flammable Limits in Air: NONE.

SECTION VI: REACTIVITY DATA

Conditions to Avoid:

NONE

Hazardous Polymerization: N/A**Conditions to Avoid:**

NONE

Hazardous Decomposition: N/A**Conditions to Avoid:**

NONE for Calcined Kaolin.

SECTION VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Aquatic Toxicity:

(96 hour TLM)

Aluminum III Silicate (2:1) -- over 1,000 ppm (insignificant hazard).

Hydrated Aluminum Silicate (Kaolin) -- Not listed.

SOURCE: Registry of Toxic Effects of Chemicals (July, 1980).

Procedure when Material is Released or Spilled:

NOT a "toxic pollutant" or a "hazardous substance" under Sections 307 and 311 of the Clean Water Act. Accidental releases can be cleaned up by sweeping, vacuuming or flushing with water.

Waste Disposal Method:

NOT a hazardous waste under RCRA Section 3001. Use normal solid waste disposal procedures which are in compliance with Federal, State and Local Regulations.

Additional Information:

NEUTRALIZING CHEMICALS: None Required.

SECTION VIII: SPECIAL PROTECTION INFORMATION

Ventilation:

Use sufficient general area ventilation. Local exhaust may be necessary where Threshold Limit Values (TLV's) are exceeded or dusty conditions exist.

Personal Protective Equipment:

EYE: Non-essential but desirable.

GLOVES: Non-essential.

OTHER: None.

RESPIRATORY PROTECTION: For dusty conditions wear a dust mask approved by NIOSH.

SECTION IX: SPECIAL PRECAUTIONS

Precautionary Statements/Labeling:

Accumulations on walking surfaces will cause very slippery conditions when wet.

O S H A / H M I S L A B E L	
HEALTH 0	*No Acute Effects.
FLAMMABILITY 0	None.
REACTIVITY 0	None.
MAX PERSONAL PROTECTION E	*Dust Mask.
CALCINED KAOLIN	CAS# 66402-68-4 97.50 % 99.50 %
TITANIUM DIOXIDE	CAS# 13463-67-7 0.50 % 2.50 %

*CAUTION: PROLONGED BREATHING OF EXCESSIVE DUST MAY AFFECT LUNG FUNCTION. USE DUST MASK IN DUSTY AREAS.	

J.M. HUBER CORPORATION - CLAY DIVISION - MACON, GA (912) 745-4751	

HMIS CODE: 0=Minimal ; 1=Slight ; 2=Moderate ; 3=Serious ; 4=Severe

Additional Regulatory Concerns:

CPSC: None.

USDA: None

DOT : IATA: Not restricted.

FDA : 21 CFR 186.1256; 21 CFR 176.170; et al.

OSHA

Has this product or any of its ingredients in concentrations above 0.1% been reported as a carcinogen in:

NTP? NO IARC Mono? NO OSHA Reg? NO

TSCA

Is this product, or all of its ingredients certified for inclusion on the Toxic Substances Control Act Inventory of Chemical Substances? YES

SARA304: No. SARA311: Yes.** SARA312 : Possibly

SARA313: No. NJRTRK : Yes. CAPROP65: No.

CANDSL : Yes. ECOIN : Yes. ACOIN : Yes.

RCRA : No.

STATE : Consult Local and State Hazard Communication Regulations.

Additional Information:

** Sara 311: Listed. ACGIH TLV assigned.