

**MATERIAL SAFETY DATA SHEET**

DATE: 2-99 rev: 6-2000

PREPARED BY: Jay E. Brooks

**SECTION #1**

Manufacturer's Name: MD-Both Industries

Street Address: 850 Hawthorne Lane, West Chicago, IL 60185

Emergency Telephone #: CHEMTREC 1-800-424-9300 24HRS

Product Class: Metallic Offset Ink

Trade Name: Unipak Sheetfed Silver

Product Codes: 9577, 9312, 9977, 9310, 9277, 9306, 9317, 9337, 9477, 9777, 9877, 9318, 9329, 9707**SECTION #2 HAZARDOUS INGREDIENTS**

<u>CAS Number</u>	<u>Ingredient</u>	<u>Boiling Range F</u>	<u>TLV</u>	<u>LEL</u>
64741-91-9	Light Petroleum distillate	534-592	NA	0.6%
7429-90-5	Aluminum	NA	10mg/m <sup>3</sup> (TWA as dust)	30 oz./1000ft <sup>3</sup>

All components of these products are listed in the TSCA inventory and can be found in the Canadian DSL.

**SECTION #3 PHYSICAL DATA**

Boiling range (deg. F): 534-592

Vapor density: Heavier than air

Type of odor: Mild petroleum solvent odor

Evaporation rate: Slower than butyl acetate

%VOC: Various see table below (ASTM 2369B)

Pounds/gallon 8.8 - 9.0, Density (gm/cc) 1.05 - 1.07

Liquid density: Heavier than water

Appearance: Silver colored paste

**SECTION #4 FIRE AND EXPLOSION DATA**

Flammability Classification: OSHA Class IIIB

DOT: Not regulated

Flash Point of solvent (deg. F): Minimum 210 by Pensky Martens Closed Cup.

Extinguishing Media: Foam, carbon dioxide, dry chemical, sand.

Unusual Fire and Explosion Hazards: Closed containers may explode when exposed to extreme heat. Aluminum powder may react with water to form hydrogen gas. Aluminum particles will burn at a very high temperature as a mass of material. Dry aluminum particles may explode if dispersed in air. Fire will produce dense black smoke which may contain carbon dioxide, carbon monoxide, or other hazardous combustion products.

Special Fire fighting Procedures: Water is not a suitable extinguishing medium.

**SECTION #5 HEALTH HAZARD DATA**

Effects of Overexposure:

Eye contact - May cause irritation

Skin contact - May cause dryness, irritation or dermatitis.

Inhalation - Solvent vapors may cause irritation in respiratory tract.

G:\TECH\MSDSheets\Sheetfed Inks\Unipak Sheetfed Silver.lwp page1

MARKETED BY  
**HARWICK STANDARD**  
**DISTRIBUTION CORPORATION**

60 S. Seiberling Street • Akron, Ohio 44305

**MATERIAL SAFETY DATA SHEET**

**Ingestion-** May cause aspiration of small amounts of material into lungs resulting in possible irritation of mucous membranes or central nervous system damage.

**Primary Routes of Entry:** Inhalation of solvent vapors. Skin contact

**Emergency and First Aid Procedures:**

**Eye contact:** Flush with large amounts of water for 15 minutes or until irritation subsides. If irritation persists, call physician.

**Skin contact:** Wash with soap and water. Remove and wash contaminated clothing.

**Inhalation:** Remove affected person to fresh air. Restore normal breathing.

**Ingestion:** Do not induce vomiting. Call physician.

**SECTION #6 REACTIVITY DATA**

**Product Stability:** Stable

**Conditions to avoid:** Extreme heat, sparks, open flames.

**Hazardous decomposition products:** Incomplete combustion can form carbon monoxide, smoke, or fumes.

**Hazardous polymerization will not occur.**

**SECTION #7 SPILL OR LEAK PROCEDURES**

**Procedure When Material Spilled or Released:**

Scoop up material and place in suitable container for disposal or reuse. Absorb excess solvent with sand or dry earth.

**Waste Disposal Method:**

Dispose of material in approved landfill or incinerator that can accept metal containing organic waste in accordance with local, state, and federal regulations.

**SECTION #8 SPECIAL PROTECTION INFORMATION**

**Ventilation:** Use with ventilation sufficient to prevent buildup of dangerous concentrations of solvent vapor in air.

**Protective Gloves:** Use chemical resistant gloves to avoid prolonged skin contact.

**Respiratory Protection:** Not normally required if product is used in sufficiently ventilated area.

**Eye Protection:** Goggles may help prevent eye contact.

**SECTION #9 SPECIAL PRECAUTIONS**

**Handling and Storage:** Store in closed containers in a cool, dry, well-ventilated area.

**Other Precautions:** Do not ingest. Avoid prolonged contact with skin, contact with eyes, and breathing vapor.

## MATERIAL SAFETY DATA SHEET

Product Code	% Aluminum CAS No. 7429-90-5	%VOC
9277	26	32.1
9306	23	32.9
9310	23	32.9
9317	20	35.5
9337	18	11
9477	26	6
9777, 9707	26	32.1
9877	26	32.1
9977	26	28
9577, 9318	21	28
9312	21	28
9329	17	29

The information contained in this data sheet was obtained from sources we believe are reliable but cannot guarantee. Your use of this information is beyond our control. Therefore, the information is provided without any representation or warranty.

HAZARD RATING		PRODUCT	
Minimal	0	Health	1
Slight	1	Flammability	1
Moderate	2	Reactivity	0
Serious	3	Personal Protection	B
Severe	4		