# MOMENTI\ E

# MATERIAL SAFETY DATA SHEET

Version: 1.4 03/01/2013

# SF1188A Silicone polyether copolymer

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufacturer Name: Momentive Performance Materials LLC

260 Hudson River Road Waterford NY 12188

**Revised:** 03/01/2013

Prepared by Product Safety Team 1-800-424-9300 MSDS Contact 1-888-443-9466

**Information** 4information@momentive.com

Chemical Family/Use: Silicone fluid

Formula: Polyetherpolysiloxane

**HMIS** 

Health: 1 Flammability: 1 Reactivity: 0

**NFPA** 

Health: 1 Flammability: 1 Reactivity: 0

## 2. HAZARDS IDENTIFICATION

## **EMERGENCY OVERVIEW**

Attention! This material is not considered hazardous by the OSHA Hazard Communication Standard 29 CFR 1910.1200

Form: Liquid Form: Colorless Odor: Mild

## POTENTIAL HEALTH EFFECTS

## **INGESTION**

No adverse effects are expected under normal conditions of use.

### SKIN

Causes mild skin irritation.

#### **INHALATION**

No adverse effects are expected under normal conditions of use.

## **MEDICAL CONDITIONS AGGRAVATED**

None known.

## **CHRONIC EFFECTS / CARCINOGENICITY**

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.



# MATERIAL SAFETY DATA SHEET

Version: 1.4 03/01/2013

# SF1188A Silicone polyether copolymer

#### **ROUTES OF EXPOSURE**

No anticipated routes of exposure

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION	CAS-No.	<u>WGT. %</u>
A. HAZARDOUS		
2-Propanol	67-63-0	1 - 5 %
B. NON-HAZARDOUS		
Siloxane Polyalkyleneoxide Copolymer	68937-55-3	60 - 100 %
mono-2-propenyl ether methyloxirane	9041-33-2	10 - 30 %

## 4. FIRST AID MEASURES

## **INGESTION**

If swallowed, do NOT induce vomiting. Give a glass of water. Do not give victim anything to drink if he is unconscious. Get medical attention if any discomfort continues.

### SKIN

Wash area with soap and water. Get medical attention if symptoms occur.

#### **INHALATION**

Move to fresh air. Get medical attention if symptoms persist.

## **EYES**

In the event of contact with the eyes, rinse thoroughly with clean water. Get medical attention if symptoms occur.

#### **NOTE TO PHYSICIAN**

There is no specific antidote.

# **MOMENTIVE**

# MATERIAL SAFETY DATA SHEET

Version: 1.4 03/01/2013

# SF1188A Silicone polyether copolymer

## 5. FIRE-FIGHTING MEASURES

FLASH POINT:> 100 °C; 212 °FIGNITION TEMPERATURE:No data available.FLAMMABLE LIMITS LEL:Not applicableFLAMMABLE LIMITS UEL:Not applicable

SENSITIVITY TO MECHANICAL IMPACT: No

#### SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

### **EXTINGUISHING MEDIA**

All standard extinguishing agents are suitable.

## SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

## 6. ACCIDENTAL RELEASE MEASURES

### **ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED**

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

## 7. HANDLING AND STORAGE

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Avoid contact with skin and eyes. Keep out of reach of children. Attention: Not for injection into humans. May generate formaldehyde at temperatures greater than 150 C(300 F). See Section 8 of the MSDS for Personal Protective Equipment.

### **STORAGE**

Store at room temperature in the original container. Keep container closed.



# MATERIAL SAFETY DATA SHEET

Version: 1.4 03/01/2013

# SF1188A Silicone polyether copolymer

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **ENGINEERING CONTROLS**

Provide eyewash station and safety shower.; Local exhaust is recommended.

## RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

#### **PROTECTIVE GLOVES**

Chemical resistant gloves

## **EYE AND FACE PROTECTION**

Safety glasses with side shields

## OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

## **Exposure Guidelines**

Component	CAS-No.	Source	<u>Value</u>
2-Propanol	67-63-0	OSHA Z1, PEL	400 ppm; 980 mg/m3
2-Propanol	67-63-0	ACGIH, TWA	200 ppm
2-Propanol	67-63-0	ACGIH, STEL	400 ppm
2-Propanol	67-63-0	ACGIH,	Listed.
2-Propanol	67-63-0	OSHA Z1,	Listed.

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average; INTL REL - Internal Recommended Exposure Limit

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

## 9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (°C):

VAPOR PRESSURE (20 C) (MM HG):

VAPOR DENSITY (AIR=1):

No data available.

No data available.

FREZING POINT:

No data available.

No data available.

PHYSICAL STATE: Liquid

# **MOMENTIVE**™

# MATERIAL SAFETY DATA SHEET

Version: 1.4 03/01/2013

# SF1188A Silicone polyether copolymer

ODOR: Mild
Color: Colorless
SPECIFIC GRAVITY: ca. 1.04

**DENSITY:** ca. 1.059 g/cm3

ACID / ALKALINITY (MEQ/G): ca. 0.12 pH: Not applicable

SOLUBILITY IN WATER (20 C): partly soluble
SOLUBILITY IN ORGANIC SOLVENT (STATE Soluble in toluene

SOLUBILITY IN ORGANIC SOLVENT (STATE

SOLVENT):

**VOLATILE ORGANIC CONTENT:** < 1.0 %(m)

## 10. STABILITY AND REACTIVITY

## **STABILITY**

Stable

## HAZARDOUS POLYMERIZATION.

Hazardous polymerisation does not occur.

## HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon dioxide; Silicon dioxide.; Formaldehyde.; This product contains methylpolysiloxanes which will likely generate formaldehyde at approximately 300 degrees Fahrenheit (150'C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and has been classified by the National Toxicology Program as as a known human carcinogen. A MSDS for formaldehyde is available from Momentive. See Section 11 for additional information on formaldehyde.

### **INCOMPATIBLE MATERIALS**

Avoid contact with acids and oxidizing substances.

## **CONDITIONS TO AVOID**

None known.

## 11. TOXICOLOGICAL INFORMATION

#### **ACUTE ORAL**

LD50; Species: Rat; > 5,000 mg/kg;

#### **CARCINOGENICITY**

The National Toxicology Program (NTP) classifies formaldehyde as "known to be a human carcinogen" with respect to nasopharyngeal cancer, sinonasal cancer and myeloid leukemia. The International Agency for Research on Cancer (IARC) classifies formaldehyde as "carcinogenic to humans". U.S. OSHA regulates formaldehyde as a potential human carcinogen. See the OSHA Formaldehyde Workplace Standard at 29 CFR 1920.1048 (the "OSHA Standard"). Safe handling and use instructions

# **MOMENTIVE**

# MATERIAL SAFETY DATA SHEET

Version: 1.4 03/01/2013

# SF1188A Silicone polyether copolymer

are provided in this MSDS and in the OSHA Standard. OSHA has identified 0.5 ppm, calculated as an eight-hour time-weighted average ("TWA") concentration, as the "Action Level". Please review and understand the guidance contained in this MSDS, and refer to the OSHA Standard for regulatory requirements that might be applicable to your operation and use. Many studies and other evaluations have been performed concerning formaldehyde's potential to cause cancer. To review some of these studies and for further information go to www.osha.gov; http://monographs.iarc.fr; http://ntp-server.niehs.nih.gov; http://epa.gov; http://www.nap.edu and other authoritative websites then search on formaldehyde.

## **ACUTE DERMAL**

LD50; Species: Rabbit; > 2,000 mg/kg;

#### **OTHER**

Isopropyl alcohol has produced developmental effects and reduced fetal weight in animals following inhalation exposure.

#### **SENSITIZATION**

No data available.

### SKIN IRRITATION.

Species: Rabbit; Result: Slightly irritating.. Method: Draize.

#### **EYE IRRITATION**

Species: Rabbit; Result: No eye irritation. Method: Draize.

#### MUTAGENICITY

Negative in the Ames test.

## 12. ECOLOGICAL INFORMATION

## **ECOTOXICITY**

No data available.

#### DISTRIBUTION

No data available.

## **CHEMICAL FATE**

No data available.



# MATERIAL SAFETY DATA SHEET

Version: 1.4 03/01/2013

# SF1188A Silicone polyether copolymer

## 13. DISPOSAL CONSIDERATIONS

## **DISPOSAL METHODS**

Disposal should be made in accordance with federal, state and local regulations.

## 14. TRANSPORT INFORMATION

Further Information: This product is not regarded as dangerous goods according to the national

and international regulations on the transport of dangerous goods.

## 15. REGULATORY INFORMATION

## **Inventories**

Australia Inventory of Chemical y (positive listing)

Substances (AICS)

EU list of existing chemical y (positive listing)

substances

Japan Inventory of Existing & New y (positive listing)

Chemical Substances (ENCS)

China Inventory of Existing y (positive listing)

Chemical Substances

Korea Existing Chemicals y (positive listing)

Inventory (KECI)

Canada DSL Inventory y (positive listing)
Canada NDSL Inventory n (Negative listing)
Philippines Inventory of Chemicals y (positive listing)

and Chemical Substances

(PICCS)

TSCA list y (positive listing) On TSCA Inventory

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

## **US Regulatory Information**

CERCLAReportable quantity 10000 lbs

PRODUCT COMPOSITIONChemicalCERCLA Reportable QuantityIsopropyl Alcohol67-63-0Reportable quantity: 100 LBS

SARA (311,312) HAZARD CLASS

Acute Health Hazard

**SARA (313) CHEMICALS** 

67-63-0, Isopropyl Alcohol.

# **MOMENTIVE**

# MATERIAL SAFETY DATA SHEET

Version: 1.4 03/01/2013

# SF1188A Silicone polyether copolymer

#### **CALIFORNIA PROPOSITION 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

## **Canadian Regulatory Information**

## WHMIS CLASSIFICATION

D2A - Very Toxic Material Causing Other Toxic Effects

Other

SCHDLE B/HTSUS: 3907.20 Polyethers

ECCN: EAR99

## 16. OTHER INFORMATION

## **OTHER**

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

,C = ceiling limit NEGL = negligible
EST = estimated NF = none found
NA = not applicable UNKN = unknown
NE = none established REC = recommended

ND = none determined V = recommended by vendor

SKN = skin TS = trade secret R = recommended MST = mist

NT = not tested STEL = short term exposure limit

ppm = parts per million ppb = parts per billion

By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).