

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2025
11.5	09/18/2025	20035-00030	Date of first issue: 10/08/2014

---

### SECTION 1. IDENTIFICATION

Product name : RESIMENE 3520 PJ-72

Product code : TI727

#### Manufacturer or supplier's details

Company name of supplier : Prefere Melamines LLC

Address : 730-B Worcester Street  
Springfield, USA MA 01151

Telephone : +1 888 723 2873

Telefax : +1 413 730 3444

Emergency telephone : Emergency telephone number  
(24 h / 365 d):  
+1-352-323-3500  
(GBK/Infotrac ID 92706)

E-mail address : reach-melamines@prefere.com

#### Recommended use of the chemical and restrictions on use

Recommended use : Additive  
Curing chemical  
Industrial use  
Rubber additive

Restrictions on use : Not applicable

---

### SECTION 2. HAZARDS IDENTIFICATION

**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

#### Hazards for the product as supplied

Combustible dust

Carcinogenicity : Category 1B

#### Other hazards

Dust contact with the eyes can lead to mechanical irritation.  
Contact with dust can cause mechanical irritation or drying of the skin.

#### GHS label elements

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version 11.5      Revision Date: 09/18/2025      SDS Number: 20035-00030      Date of last issue: 07/28/2025  
Date of first issue: 10/08/2014

Hazard pictograms :



Signal Word : Danger

Hazard Statements : May form combustible dust concentrations in air.  
H350 May cause cancer.

Precautionary Statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P280 Wear protective gloves, protective clothing, eye protection and face protection.  
**Response:**  
P308 + P313 IF exposed or concerned: Get medical attention.  
**Storage:**  
P405 Store locked up.  
**Disposal:**  
P501 Dispose of contents and container to an approved waste disposal plant.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture  
Chemical nature : Methylated melamine formaldehyde resin, on synthetic calcium silicate  
Special ingredients : Specification for free Formaldehyde content: 0.10 - 0.19 %

#### Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Silica gel, precipitated, crystalline free	112926-00-8*	28	-
Formaldehyde	50-00-0*	>= 0.1 - <= 0.19	-
Methanol	67-56-1*	0.13	-

\* Indicates that the identifier is a CAS No.

### SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical ad-

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2025
11.5	09/18/2025	20035-00030	Date of first issue: 10/08/2014

---

- vice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : If in eyes, rinse well with water.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May cause cancer.  
Contact with dust can cause mechanical irritation or drying of the skin.  
Dust contact with the eyes can lead to mechanical irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.  
Do not use a solid water stream as it may scatter and spread fire.  
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Nitrogen oxides (NO<sub>x</sub>)

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2025
11.5	09/18/2025	20035-00030	Date of first issue: 10/08/2014

---

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.  
Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).  
Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

Technical measures : Static electricity may accumulate and ignite suspended dust causing an explosion.  
Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.  
Do not breathe dust.  
Avoid breathing dust.

---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2025
11.5	09/18/2025	20035-00030	Date of first issue: 10/08/2014

---

Do not swallow.  
Avoid contact with eyes.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep container tightly closed.  
Minimize dust generation and accumulation.  
Keep container closed when not in use.  
Keep away from heat and sources of ignition.  
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.  
Store locked up.  
Keep tightly closed.  
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Self-reactive substances and mixtures  
Organic peroxides  
Explosives  
Gases

---

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

inert or nuisance dust	50 Million particles per cubic foot Value type (Form of exposure): TWA (total dust) Basis: OSHA Z-3
	15 mg/m <sup>3</sup> Value type (Form of exposure): TWA (total dust) Basis: OSHA Z-3
	5 mg/m <sup>3</sup> Value type (Form of exposure): TWA (respirable fraction) Basis: OSHA Z-3
	15 Million particles per cubic foot Value type (Form of exposure): TWA (respirable fraction) Basis: OSHA Z-3
Dust, nuisance dust and particulates	10 mg/m <sup>3</sup> Value type (Form of exposure): PEL (Total dust) Basis: CAL PEL

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version 11.5      Revision Date: 09/18/2025      SDS Number: 20035-00030      Date of last issue: 07/28/2025  
 Date of first issue: 10/08/2014

5 mg/m<sup>3</sup>  
 Value type (Form of exposure): PEL (respirable dust fraction)  
 Basis: CAL PEL

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Silica gel, precipitated, crystalline free	112926-00-8	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m <sup>3</sup> / %SiO <sub>2</sub> (Silica)	OSHA Z-3
		TWA	6 mg/m <sup>3</sup> (Silica)	NIOSH REL
Formaldehyde	50-00-0	TWA	0.1 ppm	ACGIH
		STEL	0.3 ppm	ACGIH
		TWA	0.016 ppm	NIOSH REL
		C	0.1 ppm	NIOSH REL
		PEL	0.75 ppm	OSHA CARC
		STEL	2 ppm	OSHA CARC
Methanol	67-56-1	TWA	0.016 ppm (Formaldehyde)	NIOSH REL
		TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		ST	250 ppm 325 mg/m <sup>3</sup>	NIOSH REL
		TWA	200 ppm 260 mg/m <sup>3</sup>	NIOSH REL
		TWA	200 ppm 260 mg/m <sup>3</sup>	OSHA Z-1

### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Formaldehyde	50-00-0	TWA	0.1 ppm	ACGIH
		STEL	0.3 ppm	ACGIH
		TWA	0.016 ppm	NIOSH REL
		C	0.1 ppm	NIOSH REL
		PEL	0.75 ppm	OSHA CARC
		STEL	2 ppm	OSHA CARC
Methanol	67-56-1	TWA	0.016 ppm (Formaldehyde)	NIOSH REL
		TWA	200 ppm	ACGIH

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version 11.5      Revision Date: 09/18/2025      SDS Number: 20035-00030      Date of last issue: 07/28/2025  
Date of first issue: 10/08/2014

		STEL	250 ppm	ACGIH
		ST	250 ppm 325 mg/m <sup>3</sup>	NIOSH REL
		TWA	200 ppm 260 mg/m <sup>3</sup>	NIOSH REL
		TWA	200 ppm 260 mg/m <sup>3</sup>	OSHA Z-1

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Minimize workplace exposure concentrations.  
Apply measures to prevent dust explosions.  
Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).  
If sufficient ventilation is unavailable, use with local exhaust ventilation.

### Personal protective equipment

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

### Hand protection

**Material** : Nitrile rubber  
**Break through time** : 240 - < 480 min  
**Glove thickness** : 0.12 mm  
**Protective index** : Class 5

**Material** : Nitrile rubber  
**Break through time** : > 480 min

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2025
11.5	09/18/2025	20035-00030	Date of first issue: 10/08/2014

---

Glove thickness : 0.38 mm  
Protective index : Class 6

Material : butyl-rubber  
Break through time : > 480 min  
Glove thickness : 0.3 mm  
Protective index : Class 6

Material : Fluorinated rubber  
Break through time : > 480 min  
Glove thickness : 0.7 mm  
Protective index : Class 6

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : colorless

Odor : formaldehyde-like

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2025
11.5	09/18/2025	20035-00030	Date of first issue: 10/08/2014

---

Initial boiling point and boiling range : No data available

Flash point : > 230 °F / > 110 °C

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper flammability limit : Not applicable

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Density : 1.46 g/cm<sup>3</sup>

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : 770 °F / 410 °C

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Dust explosion class : St1

Particle characteristics  
Particle size : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2025
11.5	09/18/2025	20035-00030	Date of first issue: 10/08/2014

---

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Dust can form an explosive mixture in air.  
Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Avoid dust formation.

Incompatible materials : Oxidizing agents

### Hazardous decomposition products

Thermal decomposition : Formaldehyde  
Methanol

---

## SECTION 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

### Acute toxicity

Not classified based on available information.

### Product:

Acute oral toxicity : Acute toxicity estimate: 3,222 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

### Components:

#### Silica gel, precipitated, crystalline free:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 0.69 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2025
11.5	09/18/2025	20035-00030	Date of first issue: 10/08/2014

---

### Formaldehyde:

Acute oral toxicity : Acute toxicity estimate: 100 mg/kg  
Method: Expert judgment

Acute inhalation toxicity : Acute toxicity estimate: 100 ppm  
Exposure time: 4 h  
Test atmosphere: gas  
Method: Expert judgment

Acute dermal toxicity : LD50 (Rabbit): 270 mg/kg

### Methanol:

Acute oral toxicity : Acute toxicity estimate (Humans): 300 mg/kg  
Method: Expert judgment

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Expert judgment  
Remarks: Based on national or regional regulation.

Acute dermal toxicity : Acute toxicity estimate: 300 mg/kg  
Method: Expert judgment  
Remarks: Based on national or regional regulation.

### Skin corrosion/irritation

Not classified based on available information.

### Components:

#### Silica gel, precipitated, crystalline free:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

### Formaldehyde:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Corrosive after 3 minutes to 1 hour of exposure

### Methanol:

Species : Rabbit  
Result : No skin irritation

### Serious eye damage/eye irritation

Not classified based on available information.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2025
11.5	09/18/2025	20035-00030	Date of first issue: 10/08/2014

---

### Components:

#### **Silica gel, precipitated, crystalline free:**

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

#### **Formaldehyde:**

Species	:	Rabbit
Result	:	Irreversible effects on the eye

#### **Methanol:**

Species	:	Rabbit
Result	:	No eye irritation

### **Respiratory or skin sensitization**

#### **Skin sensitization**

Not classified based on available information.

#### **Respiratory sensitization**

Not classified based on available information.

### Components:

#### **Formaldehyde:**

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	positive

Assessment	:	Probability or evidence of high skin sensitization rate in humans
------------	---	---

#### **Methanol:**

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative

### **Germ cell mutagenicity**

Not classified based on available information.

### Components:

#### **Silica gel, precipitated, crystalline free:**

Genotoxicity in vitro	:	Test Type: Chromosome aberration test in vitro Result: negative Remarks: Based on data from similar materials
-----------------------	---	---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2025
11.5	09/18/2025	20035-00030	Date of first issue: 10/08/2014

---

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

### Formaldehyde:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: positive

Test Type: Chromosome aberration test in vitro  
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: Inhalation  
Result: positive

Germ cell mutagenicity - Assessment : Positive result(s) from in vivo mammalian somatic cell mutagenicity tests.

### Methanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: in vitro micronucleus test  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

### Carcinogenicity

May cause cancer.

### Components:

#### **Silica gel, precipitated, crystalline free:**

Species : Rat  
Application Route : Ingestion  
Exposure time : 103 weeks  
Result : negative  
Remarks : Based on data from similar materials

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version 11.5      Revision Date: 09/18/2025      SDS Number: 20035-00030      Date of last issue: 07/28/2025  
Date of first issue: 10/08/2014

---

### Formaldehyde:

Species : Rat  
Application Route : inhalation (gas)  
Exposure time : 28 Months  
Result : positive

Carcinogenicity - Assessment : Sufficient evidence of carcinogenicity in animal experiments

### Methanol:

Species : Monkey  
Application Route : inhalation (vapor)  
Exposure time : 7 Months  
Result : negative

<b>IARC</b>	Group 1: Carcinogenic to humans Formaldehyde	50-00-0
<b>OSHA</b>	OSHA specifically regulated carcinogen Formaldehyde	50-00-0
<b>NTP</b>	Known to be human carcinogen Formaldehyde	50-00-0

### Reproductive toxicity

Not classified based on available information.

### Components:

#### **Silica gel, precipitated, crystalline free:**

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

#### **Formaldehyde:**

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (gas)  
Result: negative

#### **Methanol:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Monkey  
Application Route: inhalation (vapor)  
Result: negative

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test  
Species: Monkey

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2025
11.5	09/18/2025	20035-00030	Date of first issue: 10/08/2014

---

Application Route: inhalation (vapor)  
Result: negative

### STOT-single exposure

Not classified based on available information.

#### Components:

##### Formaldehyde:

Assessment : May cause respiratory irritation.

##### Methanol:

Target Organs : optic nerve, Central nervous system  
Assessment : Causes damage to organs.

### STOT-repeated exposure

Not classified based on available information.

#### Components:

##### Formaldehyde:

Assessment : No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

### Repeated dose toxicity

#### Components:

##### Silica gel, precipitated, crystalline free:

Species : Rat  
NOAEL : > 4,500 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

##### Formaldehyde:

Species : Rat  
NOAEL : 6 ppm  
LOAEL : 10 ppm  
Application Route : inhalation (gas)  
Exposure time : 28 Days

### Aspiration toxicity

Not classified based on available information.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2025
11.5	09/18/2025	20035-00030	Date of first issue: 10/08/2014

---

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Components:

##### **Silica gel, precipitated, crystalline free:**

- Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 10,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EL50 (Scenedesmus subspicatus): > 10,000 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

##### **Formaldehyde:**

- Toxicity to fish : LC50 : 6.7 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 5.8 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 4.89 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOEC (Oryzias latipes (Orange-red killifish)): >= 48 mg/l  
Exposure time: 28 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 6.4 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211
- Toxicity to microorganisms : EC50: 34.1 mg/l  
Exposure time: 120 h

##### **Methanol:**

- Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 15,400 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Method: DIN 38412

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2025
11.5	09/18/2025	20035-00030	Date of first issue: 10/08/2014

---

Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)):  
22,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l  
Exposure time: 3 h  
Test substance: Neutralized product  
Method: OECD Test Guideline 209

### Persistence and degradability

#### Components:

##### **Formaldehyde:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 91 %  
Exposure time: 14 d  
Method: OECD Test Guideline 301C  
Remarks: Based on data from similar materials

##### **Methanol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 95 %  
Exposure time: 20 d

### Bioaccumulative potential

#### Components:

##### **Formaldehyde:**

Partition coefficient: n-octanol/water : log Pow: 0.35

##### **Methanol:**

Bioaccumulation : Species: Leuciscus idus (Golden orfe)  
Bioconcentration factor (BCF): < 10

Partition coefficient: n-octanol/water : log Pow: -0.77

### Mobility in soil

No data available

### Other adverse effects

No data available

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version 11.5      Revision Date: 09/18/2025      SDS Number: 20035-00030      Date of last issue: 07/28/2025  
Date of first issue: 10/08/2014

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Dispose of in accordance with local regulations.  
Do not dispose of waste into sewer.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.
- 

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to IMO instruments

Not applicable for product as supplied.

#### Domestic regulation

##### 49 CFR

Not regulated as a dangerous good

#### Special precautions for user

Not applicable

---

### SECTION 15. REGULATORY INFORMATION

#### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Formaldehyde	50-00-0	100	52631

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Formaldehyde	50-00-0	100	52631

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

- SARA 311/312 Hazards** : Combustible dust  
Carcinogenicity

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2025
11.5	09/18/2025	20035-00030	Date of first issue: 10/08/2014

---

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Formaldehyde	50-00-0	>= 0.1 - <= 0.19 %
--------------	---------	--------------------

### US State Regulations

#### Pennsylvania Right To Know

1,3,5-Triazine-2,4,6-Triamine, Polymer With Formaldehyde, Methylated	68002-20-0
Silica gel, precipitated, crystalline free	112926-00-8
Formaldehyde	50-00-0
Methanol	67-56-1

#### California Prop. 65

WARNING: This product can expose you to chemicals including Formaldehyde, which is/are known to the State of California to cause cancer, and Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### California Permissible Exposure Limits for Chemical Contaminants

Silica gel, precipitated, crystalline free	112926-00-8
--	-------------

#### California Regulated Carcinogens

Formaldehyde	50-00-0
--------------	---------

#### The ingredients of this product are reported in the following inventories:

TSCA	: On or in compliance with the active portion of the TSCA inventory
CA. DSL	: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
AIIC	: All ingredients listed or exempt.
KECI	: All ingredients listed, exempt or notified.
ENCS	: On the inventory, or in compliance with the inventory
PICCS	: All ingredients listed or exempt.
ISHL	: On the inventory, or in compliance with the inventory
IECSC	: All ingredients listed or exempt.
TECI	: On the inventory, or in compliance with the inventory

---

## SECTION 16. OTHER INFORMATION

### Further information

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72


Version  
11.5

Revision Date:  
09/18/2025

SDS Number:  
20035-00030

Date of last issue: 07/28/2025  
Date of first issue: 10/08/2014

### NFPA 704:



### HMIS® IV:

HEALTH	*	1
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
CAL PEL	:	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA CARC	:	OSHA Specifically Regulated Chemicals/Carcinogens
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CAL PEL / PEL	:	Permissible exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA CARC / PEL	:	Permissible exposure limit (PEL)
OSHA CARC / STEL	:	Excursion limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## RESIMENE 3520 PJ-72

Version	Revision Date:	SDS Number:	Date of last issue: 07/28/2025
11.5	09/18/2025	20035-00030	Date of first issue: 10/08/2014

---

International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/18/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8