

SAFETY DATA SHEET



LUPEROX® 101XL45

1. PRODUCT AND COMPANY IDENTIFICATION

Company

Arkema Inc.
900 First Avenue
King of Prussia, Pennsylvania 19406

Functional Additives

Customer Service Telephone Number: (800) 331-7654
(Monday through Friday, 8:00 AM to 5:00 PM EST)

Emergency Information

Transportation: CHEMTREC: (800) 424-9300
(24 hrs., 7 days a week)
Medical: Rocky Mountain Poison Center: (866) 767-5089
(24 hrs., 7 days a week)

Product Information

Product name: LUPEROX® 101XL45
Synonyms: Dialkyl peroxide
Molecular formula: Complex Mixture
Chemical family: Organic peroxide - dialkyl peroxides
Product use: Cross-linking agent for polymers and elastomers

SECTION 2: HAZARDS IDENTIFICATION

Emergency Overview

Color: white
Physical state: solid
Form: powder
Odor: menthol

***Classification of the substance or mixture:**

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)
Combustible dust
Organic peroxides, Type E, H242
Skin irritation, Category 2, H315
Chronic aquatic toxicity, Category 3, H412

*For the full text of the H-Statements mentioned in this Section, see Section 16.

GHS-Labeling

Hazard pictograms:



Signal word:

Warning**Hazard statements:**

H242 : Heating may cause a fire.
H315 : Causes skin irritation.
H412 : Harmful to aquatic life with long lasting effects.
May form combustible dust concentrations in air.

Supplemental Hazard Statements:

Organic peroxide.
Hazardous decomposition may occur.

Precautionary statements:**Prevention:**

P210 : Keep away from heat, sparks, open flames, hot surfaces. No smoking.
P220 : Keep/Store away from clothing/ combustible materials.
P234 : Keep only in original container.
P264 : Wash skin thoroughly after handling.
P273 : Avoid release to the environment.
P280 : Wear protective gloves or eye protection or face protection.

Response:

P302 + P352 : IF ON SKIN: Wash with plenty of soap and water.
P332 + P313 : If skin irritation occurs: Get medical advice/ attention.
P362 : Take off contaminated clothing and wash before reuse.

Storage:

P410 : Protect from sunlight.
P411 + P235 : Maximum storage temperature is specified on label and in section 7 of SDS. Keep cool.
P420 : Store away from other materials.

Disposal:

P501 : Dispose of contents or container to an approved waste disposal plant.

SAFETY DATA SHEET



LUPEROX® 101XL45

Other:

Mechanical irritation effects from dust exposure are possible at ambient temperature.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS-No.	Wt/Wt	GHS Classification**
Peroxide, (1,1,4,4-tetramethyl-1,4-butanediyl)bis[(1,1-dimethylethyl)	78-63-7	>= 45 - < 49 %	H227, H242, H315
Silica gel, pptd., cryst.-free	112926-00-8	>= 22 - < 30 %	Not classified
Carbonic acid calcium salt (1:1)	471-34-1	>= 18 - < 26.5 %	Not classified
1,2-Dioxane, 3,3,6,6-tetramethyl-	22431-89-6	>= 1 - < 5 %	H226, H242, H315, H319, H335
2,4,4-Trimethylpentene	25167-70-8	>= 0.1 - < 1 %	H225, H336, H304, H400, H410

**For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: FIRST AID MEASURES
4.1. Description of necessary first-aid measures:
Inhalation:

If inhaled, remove victim to fresh air.

Skin:

In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eyes:

Product code: 054000

Version 3.1

Issued on: 01/14/2025

Page: 3 / 19

LUPEROX® 101XL45

Immediately flush eye(s) with plenty of water.

Ingestion:

If swallowed, DO NOT induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed:

For most important symptoms and effects (acute and delayed), see Section 2 (Hazard Statements and Supplemental Information if applicable) and Section 11 (Toxicology Information) of this SDS.

4.3. Indication of any immediate medical attention and special treatment needed:

Unless otherwise noted in Notes to Physician, no specific treatment noted; treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES**Extinguishing media (suitable):**

Water spray, Foam, Dry chemical

Extinguishing media (unsuitable):

High volume water jet

Protective equipment:

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand / NIOSH approved or equivalent).

Further firefighting advice:

Do not use a solid stream of water.

A solid stream of water can cause a dust explosion.

Fight fire with large amounts of water from a safe distance.

Cool closed containers exposed to fire with water spray.

Closed containers of this material may explode when subjected to heat from surrounding fire.

After a fire, wait until the material has cooled to room temperature before initiating clean-up activities.

Do not allow run-off from fire fighting to enter drains or water courses.

Fire fighting equipment should be thoroughly decontaminated after use.

Fire and explosion hazards:

Contact with materials to avoid or exposure to temperatures exceeding the SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may autoignite.

LUPEROX® 101XL45

Dust clouds generated during handling and/or storage can form explosive mixtures with air. Dust explosion characteristics vary with the particle size, particle shape, moisture content, contaminants, and other variables. Note: Check that all equipment is properly grounded and installed to satisfy electrical classification requirements. As with any dry material, pouring this material or allowing it to free-fall or to be conveyed through chutes or pipes can accumulate and generate electrostatic sparks, potentially causing ignition of the material itself, or of any flammable materials which may come into contact with the material or its container. When burned, the following hazardous products of combustion can occur:

- Carbon oxides
- Hazardous organic compounds

SECTION 6: ACCIDENTAL RELEASE MEASURES**Personal precautions, Emergency procedures, Methods and materials for containment/clean-up:**

Prevent further leakage or spillage if you can do so without risk. Evacuate area of all unnecessary personnel. Ventilate the area. Eliminate all ignition sources. Avoid dust formation and dispersal of dust in the air. Wet down (dampen) the spilled material with water. Sweep or scoop up using non-sparking tools and place into suitable properly labeled containers for prompt disposal. The sweepings should be wetted down further with water. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Implement workplace practices such that dusts are not allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

Protective equipment:

Appropriate personal protective equipment is set forth in Section 8.

SECTION 7: HANDLING AND STORAGE**Handling****General information on handling:**

Contact with materials to avoid or exposure to temperatures exceeding the SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may autoignite.

Avoid breathing dust.

Avoid contact with skin, eyes and clothing.

Keep away from heat, sparks and flames.

No smoking.

Use only with adequate ventilation.

Wash thoroughly after handling.

Prevent product contamination.

Keep container tightly closed and away from combustible materials.

Keep only in the original container.

Avoid creating dust in handling, transfer or clean up.

Prevent dust accumulation.

Implement routine housekeeping practices to ensure that dusts do not accumulate on surfaces.

Check that all equipment is properly grounded and installed to satisfy electrical classification requirements.

Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations.

Container hazardous when empty.

Follow label warnings even after container is emptied.

RESIDUAL DUSTS MAY EXPLODE ON IGNITION.

DO NOT CUT, DRILL, GRIND, OR WELD ON OR NEAR THIS CONTAINER.

Do not reuse container as it may retain hazardous product residue.

Improper disposal or reuse of this container may be dangerous and/or illegal.

Emptied container retains product residue.

Storage**General information on storage conditions:**

Keep in a dry, cool place. Store in closed containers, in a secure area to prevent container damage and subsequent spillage. Segregated or detached storage is preferred. Store in well ventilated area away from heat and sources of ignition such as flame, sparks and static electricity. Ensure that all storage and handling equipment is properly grounded and installed to satisfy electrical classification requirements. Store out of direct sunlight in a cool well-ventilated place. Store in original container. Store away from combustibles and materials to avoid. Refer also to National Fire Protection Association (NFPA) Code 400, Hazardous Materials Code. Static electricity may accumulate when transferring material. All metal and groundable storage containers, including but not limited to drums, cylinders, Returnable Intermodal Bulk Containers (RIBCs) and Class C Flexible Intermodal Bulk Containers (FIBCs) must be bonded and grounded during filling and emptying operations. Observe all federal, state and local regulations and National Fire Protection Association (NFPA) Codes, which pertain to the specific local conditions of storage and use, including NFPA 654.

Storage stability – Remarks:

Follow the recommended storage temperatures provided in this Section in order to maintain stability and oxygen content.

Storage incompatibility – General:

Store separate from:

LUPEROX® 101XL45

Engineering controls:

Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits (if applicable see above). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment. Check that all dust control equipment such as local exhaust ventilation, material transport systems, and air-material separation devices involved in handling this product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment. Isolation devices may be appropriate to prevent propagation from one unit to another. Ensure that dust-handling systems are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Consult ACGIH ventilation manual, NFPA Standard 91 and NFPA Standard 654 for design of exhaust system and safe handling.

Respiratory protection:

Avoid breathing dust. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components. Full facepiece equipment is recommended and, if used, replaces need for face shield and/or chemical goggles. Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

Skin protection:

Wear appropriate chemical resistant protective clothing and chemical resistant gloves to prevent skin contact. Consult glove manufacturer to determine appropriate type glove material for given application. Rinse immediately if skin is contaminated. Wash contaminated clothing and clean protective equipment before reuse. Provide a safety shower at any location where skin contact can occur. Wash thoroughly after handling.

Eye protection:

Where there is potential for eye contact, wear chemical goggles and have eye flushing equipment immediately available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Color:	white
Physical state:	solid
Form:	powder
Odor:	menthol
Odor threshold:	No data available
Flash point	The flashpoint of this product is greater than the Self Acceleration Decomposition Temperature (SADT).

SAFETY DATA SHEET



LUPEROX® 101XL45

Auto-ignition temperature:	No data available.
Lower flammable limit (LFL):	No data available
Upper flammable limit (UFL):	No data available
pH:	No data available
Density:	1.25 g/cm ³ measured (77 °F (25 °C)) (Method: Pycnometer)
Specific Gravity (Relative density):	No data available
Bulk density:	550 kg/m ³
Vapor pressure:	No data available.
Vapor density:	No data available.
Boiling point/boiling range:	Decomposes before boiling. Rate of decomposition increases with rising temperature.
Melting point/range:	No data available
Freezing point:	Not applicable
Evaporation rate:	No data available
Solubility in water:	insoluble
Viscosity, dynamic:	No data available
Oil/water partition coefficient:	No data available.
Self-Accelerating Decomposition Temperature (SADT):	180 °F (82 °C) 100 pound container
Thermal decomposition:	No data available
Active oxygen content:	4.96 %
Flammability:	See GHS Classification in Section 2 if applicable

SECTION 10: STABILITY AND REACTIVITY

SAFETY DATA SHEET



LUPEROX® 101XL45

Stability:

This material is chemically unstable and should only be handled under specified conditions. See HANDLING AND STORAGE section of this SDS for specified conditions.

Hazardous reactions:

Hazardous polymerization does not occur.

Materials to avoid:

Strong acids
Strong oxidizing agents
Reducing agents
Accelerators
Friedel - Crafts reaction catalyst
Brass
Copper
Iron

For all Organic Peroxides, compatible materials of contact are stainless steel 304 or 316 (preferred), high-density polyethylene (HDPE), polytetrafluoroethylene or glass linings.

Conditions / hazards to avoid:

SADT - Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction. This reaction will generate flammable vapors which may autoignite. The length of time to generate a decomposition reaction, after the SADT has been reached or exceeded, is dependent upon how much the SADT has been exceeded and the length of time needed for the reaction exotherm (heat spike from increasing decomposition rate) to initiate a rapid decomposition reaction. Typically, SADT is inversely proportional to package size. Larger packages will have a lower SADT due to smaller ratio to heat transfer area to volume of product. See HANDLING AND STORAGE section of this SDS for specified conditions. See Hazardous Decomposition Products below.

Hazardous decomposition products:

Temperatures at or above SADT can result in the release of hazardous decomposition products which are flammable and may autoignite.

Thermal decomposition giving flammable and toxic products :

Carbon oxides
Hazardous organic compounds

SECTION 11: TOXICOLOGICAL INFORMATION

Data on this material and/or its components are summarized below.

Data for LUPEROX® 101XL45**Acute toxicity****Dermal:**

Practically nontoxic. Acute toxicity estimate > 5,000 mg/kg.

Data for Peroxide, (1,1,4,4-tetramethyl-1,4-butanediyl)bis[(1,1-dimethylethyl) (78-63-7)**Acute toxicity**

LUPEROX® 101XL45

Oral:

No deaths occurred. (rat) LD₀ > 2,000 mg/kg.

Dermal:

May be harmful in contact with skin. (rabbit) LD₅₀ = 4,100 mg/kg.

Skin Irritation:

Causes skin irritation. (rabbit) (4 h)

Eye Irritation:

Causes mild eye irritation. (rabbit)

Skin Sensitization:

Not a sensitizer. Guinea pig maximization test. No skin allergy was observed

Repeated dose toxicity

Subchronic oral administration to rat / affected organ(s): kidney / signs: hyaline droplet nephropathy

Repeated oral administration to rat / affected organ(s): liver, kidney / signs: changes in organ weights, changes in organ structure or function, hyaline droplet nephropathy

Genotoxicity**Assessment in Vitro:**

No genetic changes were observed in laboratory tests using: bacteria, animal cells

Genotoxicity**Assessment in Vivo:**

No genetic changes were observed in a laboratory test using: mice

Developmental toxicity

Exposure during pregnancy. oral (rat) / No birth defects were observed.

Data for Silica gel, pptd., cryst.-free (112926-00-8)**Acute toxicity****Oral:**

Practically nontoxic. (rat) LD₅₀ > 5,000 mg/kg.

Dermal:

Practically nontoxic. (rabbit) LD₅₀ > 5,000 mg/kg.

Inhalation:

No deaths occurred. (rat) 4 h LC₀ > 2.08 mg/l. (dust/mist)

Skin Irritation:

Practically non-irritating. (rabbit) (4 h)

LUPEROX® 101XL45

Eye Irritation:

Causes mild eye irritation. (rabbit)

Skin Sensitization:

Not a sensitizer. Guinea pig maximization test. No skin allergy was observed.

Repeated dose toxicity

Repeated inhalation administration to rat / affected organ(s): lung, lymph node / signs: inflammation / No adverse systemic effects reported. (Local effects, reversible)

Subchronic dietary administration to rat / No adverse systemic effects reported.

Carcinogenicity

Chronic dietary administration to rat and mouse / No increase in tumor incidence was reported. Classified by the International Agency for Research on Cancer as: Group 3: Unclassifiable as to carcinogenicity in humans.

Genotoxicity**Assessment in Vitro:**

No genetic changes were observed in laboratory tests using: bacteria, animal cells, human cells, yeast

Genotoxicity**Assessment in Vivo:**

No genetic changes were observed in laboratory tests using: rats

Developmental toxicity

Exposure during pregnancy. Oral (rat, rabbit, hamster, mouse) / No birth defects were observed.

Reproductive effects

Two-generation study. Oral (rat) / No toxicity to reproduction.

Other information

The information presented is from representative materials in this chemical class. The results may vary depending on the test substance.

Human experience**Inhalation:**

Respiratory system: No increase in tumor incidence was reported. No significant impairment of lung function. (based on reports of occupational exposure to workers)

Data for Carbonic acid calcium salt (1:1) (471-34-1)**Acute toxicity****Oral:**

No deaths occurred. (rat) LD0 > 2,000 mg/kg.

Dermal:

No deaths occurred. (rat) LD0 > 2,000 mg/kg.

LUPEROX® 101XL45

Inhalation:

No deaths occurred. (rat) 4 h LC0 > 3 mg/l. (dust/mist, Maximum concentration technically possible)

Skin Irritation:

Not irritating. (rabbit) (4 h)

Eye Irritation:

Causes mild eye irritation. (rabbit)

Skin Sensitization:

Not a sensitizer. LLNA: Local Lymph Node Assay. (mouse) No skin allergy was observed.

Repeated dose toxicity

Repeated oral administration to rat, mouse / No adverse systemic effects reported.

Genotoxicity**Assessment in Vitro:**

No genetic changes were observed in laboratory tests using: bacteria, animal cells, human cells

Developmental toxicity

Exposure during pregnancy. Dietary (rat) / No birth defects were observed.

Reproductive effects

Reproductive/Developmental Effects Screening Assay. Oral (rat) / No toxicity to reproduction.

Human experience**General:**

Dust contact with the eyes can lead to mechanical irritation. Contact with dust can cause mechanical irritation or drying of the skin.

Human experience**Inhalation:**

Upper respiratory tract: Local irritation, coughing. (dust) (severity of effects depends on extent of exposure)

Human experience**Ingestion:**

Kidney: failure, weakness, nausea. (effects of excessive exposure)

Data for 1,2-Dioxane, 3,3,6,6-tetramethyl- (22431-89-6)**Acute toxicity****Specific target organ toxicity - single exposure:**

May cause respiratory irritation.

Skin Irritation:

Causes skin irritation. (estimate based on composition)

Eye Irritation:

Causes serious eye irritation. (estimate based on composition)

LUPEROX® 101XL45

Other information

The information presented is from representative materials in this chemical class. The results may vary depending on the test substance.

SECTION 12: ECOLOGICAL INFORMATION**Chemical Fate and Pathway**

Data on this material and/or its components are summarized below.

Data for Peroxide, (1,1,4,4-tetramethyl-1,4-butanediyl)bis[(1,1-dimethylethyl) (78-63-7)**Stability in water:**

Half-life 2.7 h (@pH 4)

Half-life 2.7 h (@pH 7)

Half-life 2.8 h (@pH 9)

Biodegradation:

Not readily biodegradable. (60 d) biodegradation 0 %

Bioaccumulation:

512 - 539 (Fish)

Octanol Water Partition Coefficient:

log Pow: = 7.34, at 68 °F (20 °C)

Data for 2,4,4-Trimethylpentene (25167-70-8)**Biodegradation:**

Not readily biodegradable. (28 d) biodegradation 1.6 %

Octanol Water Partition Coefficient:

log Pow: = 4.9, at 77 °F (25 °C) pH = 7

Ecotoxicology

Data on this material and/or its components are summarized below.

Data for Peroxide, (1,1,4,4-tetramethyl-1,4-butanediyl)bis[(1,1-dimethylethyl) (78-63-7)**Aquatic toxicity data:**

No effect up to the limit of solubility. *Oryzias latipes* (Orange-red killifish) 96 h

Algae:

No effect up to the limit of solubility. *Pseudokirchneriella subcapitata* 72 h

Microorganisms:

Activated sludge 3 h NOEC (Respiration inhibition) > 1,000 mg/l

Chronic toxicity to aquatic invertebrates:

SAFETY DATA SHEET

ARKEMA

LUPEROX® 101XL45

No effect up to the limit of solubility. *Daphnia magna* (Water flea) 21 d NOEC > 0.0065 mg/l

Chronic toxicity to aquatic plants:

No effect up to the limit of solubility. *Pseudokirchneriella subcapitata* 72 h NOEC > 0.236 mg/l

Data for Silica gel, pptd., cryst.-free (112926-00-8)

The information presented is from representative materials in this chemical class. The results may vary depending on the test substance.

Aquatic toxicity data:

No effect up to the limit of solubility. *Danio rerio* (zebra fish) 96 h LL50 > 10,000 mg/l (Nominal concentration)

Aquatic invertebrates:

No effect up to the limit of solubility. *Daphnia magna* (Water flea) 48 h EL50 > 5,000 mg/l (Nominal concentration)

Algae:

No effect up to the limit of solubility. *Desmodesmus subspicatus* (green algae) 72 h EC50 > 173 mg/l (Nominal concentration)

Chronic toxicity to aquatic plants:

No effect up to the limit of solubility. *Desmodesmus subspicatus* (green algae) 72 h NOEC = 173 mg/l (Nominal concentration)

Data for Carbonic acid calcium salt (1:1) (471-34-1)

Aquatic toxicity data:

No effect up to the limit of solubility. *Oncorhynchus mykiss* (rainbow trout) 96 h LC50 > 100 mg/l (Nominal concentration, Water accommodated fraction was tested.)

Aquatic invertebrates:

No effect up to the limit of solubility. *Daphnia magna* (Water flea) 48 h EC50 > 100 mg/l (Nominal concentration, Water accommodated fraction was tested.)

Algae:

No effect up to the limit of solubility. *Desmodesmus subspicatus* (green algae) 72 h EC50 > 14 mg/l (Water accommodated fraction was tested.)

Microorganisms:

Respiration inhibition / Activated sludge 3 h EC50 > 1,000 mg/l

Chronic toxicity to aquatic plants:

No effect up to the limit of solubility. *Desmodesmus subspicatus* (green algae) 72 h NOEC = 14 mg/l (Water accommodated fraction was tested.)

Data for 2,4,4-Trimethylpentene (25167-70-8)

Aquatic toxicity data:

Very toxic. *Oncorhynchus mykiss* (rainbow trout) 96 h LC50 = 0.58 mg/l

SAFETY DATA SHEET



LUPEROX® 101XL45

Aquatic invertebrates:

Toxic. Daphnia magna (Water flea) 48 h EC50 = 1.2 mg/l

Algae:

Toxic. Pseudokirchneriella subcapitata (green algae) 72 h ErC50 = 1.5 mg/l

Microorganisms:

Respiration inhibition / Activated sludge 28 d NOEC = 23 mg/l

Chronic toxicity to aquatic invertebrates:

Toxic. Daphnia magna (Water flea) 21 d NOEC (Reproduction inhibition) = 0.16 mg/l

Chronic toxicity to aquatic plants:

Practically nontoxic. Pseudokirchneriella subcapitata (green algae) 72 h EC10 = 1.3 mg/l

SECTION 13: DISPOSAL CONSIDERATIONS

Waste disposal:

Disposal via incineration is recommended. Dispose of in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

Take appropriate measures to prevent release to the environment.

SECTION 14: TRANSPORT INFORMATION

US Department of Transportation (DOT)

UN Number : 3108
Proper shipping name : Organic peroxide type E, solid
Technical name : (2,5-Dimethyl-2,5-di(tert-butylperoxy) hexane, <=77%)
Class : 5.2
Marine pollutant : no

International Maritime Dangerous Goods Code (IMDG)

UN Number : 3108
Proper shipping name : ORGANIC PEROXIDE TYPE E, SOLID
Technical name : (2,5-DIMETHYL-2,5-DI(TERT-BUTYLPEROXY) HEXANE, <=77%)
Class : 5.2
Marine pollutant : no

SECTION 15: REGULATORY INFORMATION

SAFETY DATA SHEET



LUPEROX® 101XL45

Chemical Inventory Status

US. Toxic Substances Control Act	TSCA	The components of this product are all on the Active TSCA Inventory.
Canadian Domestic Substances List (DSL)	DSL	All components of this product are on the Canadian DSL
China. Inventory of Existing Chemical Substances in China (IECSC)	IECSC (CN)	All components of this product are listed or exempted
Japan. ENCS - Existing and New Chemical Substances Inventory	ENCS (JP)	Not all components of this product are listed or exempted
Japan. ISHL - Inventory of Chemical Substances	ISHL (JP)	All components of this product are listed or exempted
Korea. Korean Existing Chemicals Inventory (KECI)	KECI (KR)	All components of this product are listed or exempted
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	PICCS (PH)	All components of this product are listed or exempted
Australian Inventory of Industrial Chemicals	AU AIICL	Not all components of this product are listed or exempted
Taiwan Chemical Substance Inventory (TCSI)	TCSI	Not all components of this product are listed or exempted

United States – Federal Regulations**SARA Title III – Section 302 Extremely Hazardous Chemicals:**

The components in this product are either not SARA Section 302 regulated or regulated but present in negligible concentrations.

SARA Title III - Section 311/312 Hazard Categories:

Organic peroxides
Combustible dust
Skin corrosion or irritation

SARA Title III – Section 313 Toxic Chemicals:

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantity (RQ):

The components in this product are either not CERCLA regulated, regulated but present in negligible concentrations, or regulated with no assigned reportable quantity.

Product code: 054000

Version 3.1

Issued on: 01/14/2025

Page: 17 / 19

SAFETY DATA SHEET



LUPEROX® 101XL45

United States – State Regulations

California Prop. 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

Chemical name
Quartz (SiO₂)

CAS-No.
14808-60-7

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H227 Combustible liquid.
- H242 Heating may cause a fire.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

Miscellaneous:

Other information: Refer to National Fire Protection Association (NFPA) Code 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

Latest Revision(s):

Reference number: 200014283
Date of Revision: 01/14/2025
Date Printed: 01/14/2025

LUPEROX® is a registered trademark of Arkema Inc.

All information contained herein is believed to be accurate as of the date of publication, is provided "as-is" and is subject to change without notice. This is not a warranty, an agreement, or substitute for expert or professional advice. Arkema Inc. ("Company") expressly disclaims and assumes no liability for the use of the products or reliance on this information. It is the sole responsibility of the user to determine the suitability of any products for user's application(s). NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED (INCLUDING SUITABILITY FOR USE IN ANY MEDICAL DEVICE OR MEDICAL APPLICATION), IS MADE CONCERNING THE PRODUCTS OR THE INFORMATION PROVIDED HEREIN. The information provided relates only to the specific products designated herein and may not be valid where such products are used in combination with other materials or in any process. The performance of the product, its shelf life, and application characteristics depends on many variables, and changes in these variables can impact product performance. You are responsible to test the suitability of any product in advance for any intended use or application and before commercialization.

SAFETY DATA SHEET



LUPEROX® 101XL45

Nothing herein shall be construed as a license for the use of any product in a manner that might infringe any patent and it should not be construed as an inducement to infringe any patent. Please carefully review the Safety Data Sheet for the product.

The Company adheres to a strict policy that applies to the use of any of its products in medical device applications. This policy can be found at <https://www.arkema.com/global/en/social-responsibility/innovation-and-sustainable-solutions/responsible-product-management/medical-device-policy/> which is incorporated herein by reference and made a part hereof. Except as expressly authorized, the Company (i) has designated specific medical grade compositions for products used in medical device applications and Company products not so designated are not authorized for use in medical device applications and (ii) strictly prohibits the use of any of its products in medical device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Company does not design, manufacture and/or directly sell any medical devices. The Company does not co-design, or offer assistance to any purchaser of its products, in their design, manufacture and/or sale of products for medical devices. It is the sole responsibility of the manufacturer of medical devices to determine the suitability of all raw material, products and components, including any medical grade products, in order to ensure that the medical device is safe for end-use and complies with all applicable legal and regulatory requirements and to conduct all necessary tests and inspections.

