
# **LUPEROX®** ATC50

## Benzoyl Peroxide Paste

### **Introduction and Applications**

Luperox® ATC50 benzoyl peroxide paste is a very low water content BPO paste. Luperox® ATC50 paste is recommended for use in specialty adhesives, silicones, and hybrid polyurethane resins used in molded composites. As compared with using dry BPO powder, Luperox® ATC50 paste offers similar low water content with easier handling and storage.



#### **Product Description**

Chemical Name	CAS-No.	Wt/Wt
dibenzoyl peroxide	94-36-0	50-52 %
tricresyl phosphate	1330-78-5	46-48 %
hydrophobic fumed silica	68611-44-9	2 %

#### **Standard Specifications**

assay	50.0 – 52.0 %
active oxygen	3.30 – 3.44 %

# Typical Physical Properties

viscosity, brookfield	ca. 55,000 cps (22°C)	
density	1.20 g/cc (22°C)	

Time	Deg C	Deg F
10 hours	72.9	163.3
1 hour	91.7	197.1

#### Half-Life Data

Half-life can be defined as the time required at a specific temperature, to affect a loss of one-half of the peroxide's active oxygen content. The efficiency of a free radical initiator depends upon its rate of decomposition.

Half-life data can be a useful guide in selecting the optimum initiator for a specific application. Several factors apply to half-life data obtained in dilute solution:

- (a) Use only applies to thermolytic decomposition
- (b) Half-life varies in different solvents due to induced decomposition if no radical scavenger is present

## **Temperature Tolerance**

Do not store above: 38°C (100°F)

#### **Shelf-Life**

Luperox® ATC50 has a shelf-life of 6 months from the date of Arkema delivery if stored at 35° to 85°F.

#### **Packaging**

Luperox® ATC50 is packaged in 5-gallon pails.

#### **Availability**

Luperox® ATC50 is available in North America from Arkema and authorized distributors.

To discuss availability or speak to a salesperson, please call 844-LUPEROX.

#### **LUPEROX® ORGANIC PEROXIDES WORLDWIDE**



The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, ARKEMA expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement. See SDS for Health & Safety Considerations. Arkema has implemented a Medical Policy regarding the use of Arkema products in Medical Devices applications that are in contact with the body or circulating bodily fluids: (http://www.arkema.com/en/social-responsibility/responsible-product-management/medical-device-policy/index.html).

Arkema has designated Medical grades to be used for such Medical Device applications. Products that have not been designated as Medical grades are not authorized by Arkema for use in Medical Device applications that are in contact with the body or circulating bodily fluids. In addition, Arkema strictly prohibits the use of any Arkema products in Medical Device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Arkema trademarks and the Arkema name shall not be used in conjunction with customers' medical devices, including without limitation, permanent or temporary implantable devices, and customers shall not represent to anyone else, that Arkema allows, endorses or permits the use of Arkema products in such medical devices. It is the sole responsibility of the manufacturer of the medical device to determine the suitability (including biocompatibility) of all raw materials, products and components, including any medical grade Arkema products, in order to ensure that the final end-use product is safe for its end use; performs or functions as intended; and complies with all applicable legal and regulatory requirements (FDA or other national drug agencies). It is the sole responsibility of the manufacturer of the medical device to conduct all necessary tests and inspections and to evaluate the medical device under actual end-use requirements and to adequately advise and warn purchasers, users, and/or learned intermediaries (such as physicians) of pertinent risks and fulfill any postmarket surveillance obligations. Any decision regarding the appropriateness of a particular Arkema material in a particular medical device should be based on the judgment of the manufacturer, seller, the competent authority, and the treating physician. Luperox®, Vulcup®, and DiCup® are registered trademarks of Arkema Inc.

© 2016 Arkema Inc. All rights reserved.



+01 844 LUPEROX

luperox.com

Arkema Inc. 900 First Avenue King of Prussia, PA 19406 USA Tel.: (+1) 610 205 7000 Arkema (China) Investment Co., Ltd. - Shanghai 6/F Block 1, Life Hub@Daning 1868 Gonghexin Road 200072 Shanghai, China Tel: (+86) 21 6147 6888 **Headquarters: Arkema France** 420, rue d'Estienne d'Orves

92705 Colombes Cedex – France Tel.: +33 (0)1 49 00 80 80 Fax: +33 (0)1 49 00 83 96 arkema.com