

## NATROCHEM INC. P.O. BOX 1205 SAVANNAH, GA 31402 (912) 236-4464 FAX: (912) 236-1919

## DATA SHEET NATRO-CEL<sup>®</sup> C60-A

Natro-Cel C60-A is a low viscosity high chlorine content chlorinated paraffin absorbed on silicon dioxide. Because of its excellent heat stability and compatibility this produce is widely used in PVC formulations as a plasticizer to increase flame retardancy. Natro-Cel C60-A with Its high chlorine content and low viscosity makes an excellent choice for many cutting oil applications. This product also finds many applications in the paint, rubber and fabric coating industries.

TEST	TEST METHOD	SPECIFICATIONS
Actives Content, %	QCL-8.2.4-2-1	76 - 80
Carrier Content, %	QCL-8.2.4-2-1	20 - 24

## **TYPICAL PROPERTIES:**

Actives Content, % Carrier Content, % Specific Gravity (Apparent) Packaging Color 78 22 1.458 50# Net Multi-wall Bags Off White

Date of Revision: 08/22/03

The information in this data sheet is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of these data or the use of this product, nor are any statements in this bulletin intended as recommendations to use our products in the infringement of any patents.

## **OTHER NATROCHEM PRODUCTS**

DLC<sup>®</sup> s - Galex<sup>®</sup> - Rosin Oils - Rosin Pitches - Tarenes<sup>™</sup> Natro-Flex<sup>™</sup> - Tar-Cel<sup>®</sup> - Natro-Cel<sup>®</sup>