AND AR

Product Literature

ISO 9001:2008 REGISTERED

STAN-LUBE/DUOPRIME® SPECIALTY TECHNICAL AND FOOD GRADE PARAFFINIC WHITE OILS

.....

Stan-Lube Technical products are all clean Technical Grade white oils that can be used in very color critical applications. These products are FDA regulated under 21 CFR 178.3620(b).

Duoprime 350 is produced using severe hydrogenation in a unique two-stage hydrotreating process and is a food grade white mineral oil. This product is FDA regulated under 21 CFR 172.878 and 178.3620(a) and also meets current standards of National Formulary and US Pharmacopeia (USP) registered as 3H and H1 lubricants. In addition, Duoprime 350 is certified to ANSI/NSF Standard 60. Duoprime 350 can all be used in color critical as well as food contact applications.

TYPICAL PROPERTIES OF STAN-LUBE WHITE MINERAL OILS

			DUOPRIME
Properties	<u>6006</u>	<u>6056</u>	350
Viscosity, SUS @ 100°F/40°C	71	553	350
Viscosity, cSt @ 100°F/40°C	13	107	67.5
API Gravity @ 60°F	34.8	30	30.5
Specific Gravity 60°/60°F	0.84	0.87	0.87
Color, Saybolt	+30	+30	+30
Flash Point (°C) COC	185	263	221
Pour Point (°C)	-25	-20	-22.4

7/31/98 - Revised 7/15/16

HARWICK STANDARD MAKES NO WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE GOODS OR USES OF THE GOODS OR PERFORMANCE OF THE GOODS AND MAKES NO WARRANTIES OF THE FITNESS FOR PARTICULAR PURPOSE OR MERCHANTABILITY. BUYER ACKNOLEDGES THAT HARWICK STANDARD WILL NOT BE LIABLE FOR CONSEQUENTIAL, INCIDENTAL, DIRECTO OR SPECIAL DAMAGES ARISING, DIRECTLY OR INDIRECTLY, IN RESPECT TO SUCH GOODS OR THE USE OR FAILURE TEHEREOF, WHETHER BASED ON BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILTY IN TORT OR OTHERWISE.