

60 S. SEIBERLING ST.
P.O. BOX 9360
AKRON, OH 44305-0360
PHONE: (330) 798-9300
FAX: (330) 798-0214
TECHNICAL FAX: (330) 798-9328
SALES FAX: (330) 798-4089
WWW.HARWICKSTANDARD.COM

ISO 9001-2000 REGISTERED

## **STAN-WAX GKD**

Stan-Wax GKD is a low molecular weight polyethylene that is supplied to the rubber industry as a low-cost processing aid. It is used as an internal process aid when compounding general purpose SBR, NR, EPDM and specialty types of polymers including CR, CSPE, and CPE. This product can be used at a typical level of 3-5 phr to impart good release characteristics and provide smooth appearance to cured rubber products.

## TYPICAL PROPERTIES

| Appearance                       | White Pellet |
|----------------------------------|--------------|
| Softening Point, Ring & Ball, °C | 104          |
| Viscosity at 125°C, cps          | 475          |
| Specific Gravity                 | 0.91         |
| Molecular Weight, Approximate    | 2800         |

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA THAT ARE BELIEVED TO BE ACCURATE AND RELIABLE. APPLICATION AND PERFORMANCE INFORMATION ARE PROVIDED ONLY AS A GUIDE, SINCE THE CONDITIONS OF USE ARE BEYOND THE CONTROL OF HARWICK STANDARD DISTRIBUTION CORPORATION. CONSEQUENTLY, HARWICK STANDARD MAKES NO WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE GOODS OR USES OF THE GOODS OR THE PERFORMANCE OF THE GOODS AND MAKES NO WARRANTIES OF FITNESS FOR PARTICULAR PURPOSE OR MERCHANTABILITY. BUYER ACKNOWLEDGES THAT HARWICK STANDARD WILL NOT BE LIABLE FOR CONSEQUENTIAL, INCIDENTAL, DIRECT OR SPECIAL DAMAGES ARISING, DIRECTLY OR INDIRECTLY, IN RESPECT TO SUCH GOODS OR THE USE OR FAILURE THEREOF, WHETHER BASED ON BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY IN TORT OR OTHERWISE.