TempRite® 677X670





PRODUCT DATA SHEET

		UNITS	VALUE	Method
Weight percent chlorine		%	67.1	
Intrinsic Viscosity			0.68	ASTM D1243
Vicat B softening temperature		°C	144	ASTM D1525
Glass Transition Temperature		°C	127	DSC
Molecular Weight	M _n M _w M _z		47000 109000 175000	GPC
Particle Size Analy	sis > 1 micron > 75 microns > 106 microns > 150 microns > 177 microns > 250 microns > 425 microns	vol%	1 4 32 24 34 5 0	laser diffraction
Average particle size		microns	166	laser diffraction
Apparent bulk density		g/cm ³ lb/ft ³	0.52 32.4	
K value by polymerization degree			57	
Specific gravity			1.57	ASTM D792

677X670ii

8 Nov 2019

This document does not represent a product specification. The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the applications disclosed. Full-scale testing and end product performance are the responsibility of the user. Lubrizol Advanced Materials, Inc. shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Lubrizol Advanced Materials, inc.'s direct control. The SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner.