ARLANXEO Performance Elastomers

Keltan ® 7752C

Version 1.0	Revision Date: 11/15/2018		DS Number: 3000006489	Date of previous issue: - Country / Language: US / EN	
SECTION 1. IDENTIFICATION					
Product name		:	Keltan ® 7752C		
Materia	al number	:	57135565		
Recommended use		:	crude product for	the production of technical rubber articles	
Manufacturer or supplier's details			iils		
Supplier		:	ARLANXEO USA LLC 111 RIDC Park West Drive PITTSBURGHPA 15275-1112 USA		
Telephone :		:	+18005269377 For information: US/Canada +14128091000 International		
Emergency telephone :		Chemtrec (800) 4 International (703 Lanxess Emerger			

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200).

The polymer is not hazardous in the form in which it is placed on the market as long as the hazardous component is included in the polymer matrix.

GHS label elements

The polymer is not hazardous in the form in which it is placed on the market as long as the hazardous component is included in the polymer matrix.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature	•	Ethylene-propylene-diene-rubber (EPDM), oil extended

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy	64742-54-7	>= 10 - < 20
paraffinic		

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

If inhaled	:	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	:	Wash off with soap and water. Get medical attention if symptoms occur.



Keltan ® 7752C

Version 1.0	Revision Date: 11/15/2018		S Number: 3000006489	Date of previous issue: - Country / Language: US / EN	
In case of eye contact		:	•	n water as a precaution. tention if symptoms appear.	
If swallowed		:	Get medical attention if symptoms appear.		
Most important symptoms a		s and	effects, both a	cute and delayed	
Sy	Symptoms		Skin: Reddeni	ng, burning, and possible permanent damage.	
Ef	fects	:	Contact with h	ot material causes thermal skin burns.	

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media :	Water spray Foam Dry chemical Carbon dioxide (CO2) Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Unsuitable extinguishing : media	None known.
Specific hazards during fire : fighting	Toxic and irritating gases/fumes may be given off during burn- ing or thermal decomposition.
Hazardous combustion prod- : ucts	Carbon dioxide (CO2) Carbon monoxide
Further information :	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment : for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	No action shall be taken involving any personal risk or without suitable training. Put on appropriate personal protection equipment. Do not touch or walk through spilled material. Evacuate personnel to safe areas. Keep unnecessary and unprotected personnel from entering.
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Methods and materials for	:	Move containers from spill area.

Keltan ® 7752C



Version 1.0	Revision Date: 11/15/2018	SDS Number: 103000006489	Date of previous issue: - Country / Language: US / EN
containment and cleaning up		beled waste Dispose of Do not allow surface wat	sweep up material and place in a designated, la- e container. wastes in an approved waste disposal facility. v spilled material or wash water to enter sewers, ers, or groundwater systems.
	Advice on safe handling		ntaminated clothing and protective equipment be- g eating areas. ould wash hands and face before eating, drinking g. opriate personal protection equipment. king and smoking should be prohibited in areas naterial is handled, stored and processed.
Cond	litions for safe storage	Store in orig dry, cool an materials (s Keep conta Containers and kept up Do not store Use approp tion.	n moisture. cordance with local regulations. ginal container protected from direct sunlight in a d well-ventilated area, away from incompatible ee Section 10) and food and drink. iner closed when not in use. that have been opened must be carefully resealed right to prevent leakage. e in unlabeled containers. riate container to avoid environmental contamina- from direct sunlight or strong incandescent light.
Reco perat	mmended storage tem- ure	Protect fron : < 86 °F (< 3	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis	
Distillates (petroleum), hy- drotreated heavy paraffinic	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1	
		TWA (Inhal- able fraction)	5 mg/m3	ACGIH	
Engineering measures	: Good general ventilation should be sufficient to control work- er exposure to airborne contaminants.				



Keltan ® 7752C

Version 1.0	Revision Date: 11/15/2018		DS Number: 3000006489	Date of previous issue: - Country / Language: US / EN	
	onal protective equipm	ent			
Respiratory protection		:	Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.		
Hand	Hand protection				
Re	Remarks		Wear suitable glo	ves.	
Eye p	Eye protection		Safety glasses with side-shields		
Skin	Skin and body protection :		Wear suitable protective clothing.		
Hygiene measures :		chemical products lavatory and at the	arms and face thoroughly after handling s, before eating, smoking and using the e end of the working period. ash stations and safety showers are close location.		

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	solid
Appearance	:	bales
Color	:	white
Odor	:	slight, characteristic
Odor Threshold	:	No data available
рН	:	No data available
Melting point/freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	No data available
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	> 698 °F (> 370 °C) Autoignition temperature
Burning number	:	1 (68 °F (20 °C))
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit	:	No data available

Keltan ® 7752C



Versi 1.0	on	Revision Date: 11/15/2018		S Number: 3000006489	Date of previous issue: - Country / Language: US / EN
\	Vapor p	oressure	:	No data available	
I	Relative	e vapor density	:	No data available	9
I	Relative	e density	:	No data available	9
I	Density		:	No data available)
Ś	Solubility(ies) Water solubility		:	insoluble	
-	Partition coefficient: n- octanol/water		:	No data available	9
I	Ignition temperature		:	No data available	
I	Decomposition temperature		:	> 572 °F (> 300 °	°C)
Ň	Viscosity		:	No data available	
I	Explosi	ve properties	:	No data available)
(Oxidizing properties		:	No data available)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	The product is stable.
Possibility of hazardous reac- tions	:	None known.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	No specific data.
Hazardous decomposition protection for the the the the term of ter		ucts Caused by smouldering and incomplete combustion toxic fumes mainly consisting of CO and CO2 may be developed. Degradation products of the polymers and their additives may also be formed.

SECTION 11. TOXICOLOGICAL INFORMATION

The most important known symptoms and effects are described in Section 2 and/or Section 4.



Keltan ® 7752C

/ersion I.0	Revision Date: 11/15/2018	SDS Number: 103000006489	Date of previous issue: - Country / Language: US / EN
Inhala	nation on likely route ation contact	es of exposure	
	e toxicity assified based on avai	ilable information.	
Com	oonents:		
Distil	lates (petroleum), hy	drotreated heavy par	raffinic:
Acute	oral toxicity	: LD50 (Rat): > 5	5,000 mg/kg
Acute	inhalation toxicity	: LC50 (Rat): > 5 Exposure time: Test atmosphe Assessment: T tion toxicity	: 4 h
Acute	dermal toxicity	: LD50 (Rabbit):	> 5,000 mg/kg
Not c	corrosion/irritation assified based on avai ponents:	ilable information.	
	lates (petroleum), hyd t: No skin irritation	drotreated heavy par	raffinic:
	us eye damage/eye in assified based on ava		
<u>Com</u>	oonents:		
	lates (petroleum), hy t: No eye irritation	drotreated heavy par	raffinic:
Resp	iratory or skin sensit	ization	
-	sensitization assified based on avai	ilable information.	
	iratory sensitization assified based on avai	ilable information.	
	cell mutagenicity assified based on avai	ilable information.	
	nogenicity assified based on avai	ilable information.	
Com	oonents:		
	lates (petroleum), hy nogenicity - Assess-		raffinic: ed on DMSO extract content < 3% (Regulation



Keltan ® 7752C

Version 1.0	Revision Date: 11/15/2018	SDS Number: 103000006489	Date of previous issue: - Country / Language: US / EN		
ment		(EC) 1272/2008, A	Annex VI, Part 3, Note L)		
IARC		No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.			
OSHA		No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.			
NTP		No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.			

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Assessment: May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Under the recommended processing conditions small amounts of emitted substance (e.g. residual monomers, residual solvents, decomposition products) may be discharged. According to our experience and information the product has no harmful effects on health if properly handled.

The substance(s) listed in Chapter 3 is/are encapsulated in this preparation in a polymer and is/are therefore not bioavailable.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:



Keltan ® 7752C

/ersion .0	Revision Date: 11/15/2018		9S Number: 3000006489	Date of previous issue: - Country / Language: US / EN			
Toxici	Toxicity to fish		 LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l End point: mortality Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: water extractable fraction 				
	ty to daphnia and other ic invertebrates	:	End point: Immob Exposure time: 48 Method: OECD To	3 h			
Toxici	ty to algae	:	EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l End point: Biomass Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: water extractable fraction				
Ecoto	xicology Assessment						
Acute	aquatic toxicity	:	No toxicity at the	limit of solubility.			
Chron	ic aquatic toxicity	:	: This product has no known ecotoxicological effects.				
Persis	stence and degradabili	ity					
Comp	oonents:						
Distill	ates (petroleum), hydr	otro	eated heavy paraf	finic:			
Biode	gradability	:	Result: Not readily	y biodegradable.			
Bioac	cumulative potential						
Comp	oonents:						
	ates (petroleum), hydr	otro	eated heavy paraf	finic:			
Partiti	on coefficient: n- ol/water	:	log Pow: > 6				
Mobil	ity in soil						
	ta available						
Other	adverse effects						
<u>Produ</u>	<u>ict:</u>						
Addition mation	onal ecological infor- n	:	sistency and insol	actically insoluble in water. In view of its cor lubility in water, no ecological problems are the product is properly handled. This produc legradable.			

SECTION 13. DISPOSAL CONSIDERATIONS



Keltan ® 7752C

Version 1.0	Revision Date: 11/15/2018		DS Number: 3000006489	Date of previous issue: - Country / Language: US / EN
	- Resource Conserva- d Recovery Authoriza- t	:	, , ,	
Dispos	al methods	:	 The generation of waste should be avoided or minimize wherever possible. Waste disposal should be in accordance with existing a state, provincial and/or local environmental controls. This material and its container must be disposed of in a way. Empty containers retain product residue; observe all putions for product. Avoid dispersal of spilled material and runoff and contasoil, waterways, drains and sewers. 	

SECTION 14. TRANSPORT INFORMATION

Domestic regulation

DOT Not regulated as a dangerous good

International Regulations

IATA-DGR Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

CERCLA

None

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Massachusetts Right To Know



Keltan ® 7752C

Version 1.0	Revision Date: 11/15/2018	SDS Number: 103000006489		previous issue: - y / Language: US / E	N
	Distillates (petrole finic	64742-54-7	10 - 20		
Penns	sylvania Right To Kn	ow			
	Ethylene Propylene Diene Rubber Distillates (petroleum), hydrotreated heavy paraf- finic				80 - 90 10 - 20

California Prop. 65

WARNING: This product can expose you to chemicals including Hexane, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Any chemical(s) listed above which do not appear elsewhere on this SDS are contained in this product at concentrations below 0.01%.

TSCA inventory

TSCA

: On TSCA Inventory


TSCA list

No substances are subject to a Significant New Use Rule.


No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

LANXESS' method of hazard communication is comprised of Product Labels and Safety Data Sheets. HMIS and NFPA ratings are provided by LANXESS as a customer service.

Revision Date : 11/15/2018



Keltan ® 7752C

Version	Revision Date:	SDS Number:	Date of previous issue: -
1.0	11/15/2018	10300006489	Country / Language: US / EN

This information is furnished without warranty, express or implied. This information is believed to be accurate to the best knowledge of our knowledge. The information provided in this Safety Data Sheet (SDS) is correct to the best of our knowledge, information and belief at the date of its publication. We assume no legal responsibility for use of or reliance upon the information in this SDS.