

# Therm-Chek® 835

# Stabilizer Product Profile

#### **Product Description**

Therm-Chek® 835 is a modified liquid tin maleate PVC Stabilizer

Therm-Chek® 835 has excellent long-term moderate temperature heat and liquid stability. It is used in coil coatings, automotive sealants, and specialty flooring applications.

Use levels are typically 2 & 4 Phr. Therm-Chek® 835 does not need ESO as a co-stabilizer.

## Safety and Handling

Complete toxicity and handling information can be found on the Material Safety Data Sheet, which is available on request.

## **Typical Properties**

Physical State	Clear pale liquid
Density (lbs./gal.)	9.6
Viscosity (Gardner)	G
Color (Gardner)	4

VALTRIS SPECIALTY CHEMICALS 7500 E. Pleasant Valley Rd. Independence, Ohio 44131 Phone (216) 875-7200 Fax (216) 875-7201 9/10/2001; r 12/7/2015

The information contained in this data sheet has been determined through the application of accepted engineering practice and is believed to be reliable Since the conditions of application and use of our products are beyond our control, no warranty is expressed or implied regarding accuracy of this information, the results to be obtained from the use of the product, so that such use will not infringe on any patent This information is furnished with the express condition that you will make your own tests to



harwickstandard.com